

- 1974 SPEAKER WIRE LOCATIONS -

<u>31 CB T</u>	50" off floor 5" rear of rear end seam	50" off floor 5" rear of rear end seam
<u>31 CB D</u>	Same as twin	
<u>31 FB T</u>	50" above floor 46" Forward rear end seam	50" above floor 46" Forward rear end seam
<u>31 FB D</u>	50" off floor 46" Forward rear end seam	50" off floor 73" Forward rear end seam
<u>29 CB T</u>	50" off floor 5" rear of rear end seam	50" off floor 5" rear of rear end seam
<u>29 CB D</u>	Same as twin	
<u>29 FB T</u>	50" off floor 32" Forward rear end seam	50" off floor 32" Forward rear end seam
<u>29 FB D</u>	50" off floor 8" Forward rear end seam	50" off floor 48" Forward rear end seam
<u>27 FB T</u>	50" off floor 20" Forward rear end seam	50" off floor 20" Forward rear end seam
<u>27 FB D</u>	50" off floor 20" Forward rear end seam	50" off floor 48" Forward rear end seam
<u>25 T</u>	50" off floor 17" Forward rear end seam	50" off floor 17" Forward rear end seam
<u>25 D</u>	50" off floor 6" Forward rear end seam	50" off floor 36" Forward rear end seam

(Continued....)